



## Save time and cost on your work site

Spray Guard® Stabilized Mulch Matrix\* (SMM) is a new product made to stabilize soils on all types of construction and building sites.

The wood fibers and exclusive soil bonding agent immediately creates a stable soil surface. And, unlike some stabilizer products that need on-site blending, Spray Guard® SMM comes pre-blended and ready for quick and easy hydraulic application...

Saving you time *and* money.



## Choose Spray Guard® SMM when:

- 💧 Steep or rugged terrain make soil preparation difficult or impossible.
- 💧 Moderate slopes or surface flows require erosion protection for up to six months.
- 💧 Nearby wildlife habitat or residential areas need nontoxic solutions.
- 💧 Cost-effectiveness, timeliness, results and quality are required.

With its accurate chemistry, trust Spray Guard® SMM to produce Easy, Consistent and Reliable results.

Contact Mat, Inc. At 1-888-477-3028  
or visit our website at [www.matinc.biz](http://www.matinc.biz)  
and learn more about how Spray Guard®  
can help you hold your ground.



Quality Erosion Control Products



\* Spray Guard® is a Stabilized Mulch Matrix (SSM) as defined by the Erosion Control Technology Council (ECTC).

## Reliable Features Reduce Overall Costs

### WORKS ON CHALLENGING TERRAIN

THE FIBERS CONTOUR TO ANY SURFACE, PROVIDING INTIMATE SOIL CONTACT AND EROSION PROTECTION EVEN DURING MODERATE RAINS. SPRAY GUARD® SMM WORKS PERFECTLY ON MODERATE SLOPES. IT ADHERES TO VIRTUALLY ALL SOIL TYPES IMMEDIATELY AND WILL REMAIN EFFECTIVE THROUGH MULTIPLE RAINFALLS.

### FORMS AN IMMEDIATE EROSION CONTROL BLANKET

SPRAY GUARD® SMM PREVENTS SOIL LOSS COMPARABLE TO MOST INTERMEDIATE EROSION CONTROL PRODUCTS. IT ABSORBS MOISTURE IMMEDIATELY AND INCREASES PERFORMANCE AS IT CURES, PROVIDING OUTSTANDING EROSION PROTECTION FOR UP TO SIX MONTHS. THE PRE-BLENDED MIXTURE MEANS YOU GET CONSISTENT PERFORMANCE. YOU WON'T NEED TO WORRY ABOUT CREATING THE RIGHT COMBINATION FOR YOUR SITE. JUST PLACE SPRAY GUARD® SMM ON YOUR WORK SITE...LEAVE THE REST TO US.

### SAFE FOR THE ENVIRONMENT

THE SPECIALLY FORMULATED MATERIAL WON'T HARM THE ENVIRONMENT OR WILDLIFE. IT'S NON-TOXIC, COMPLETELY BIODEGRADABLE AND ACTUALLY ENRICHES THE SOIL OVER TIME. YOU WON'T WORRY ABOUT HARMING FISH OR WILDLIFE. IN FACT, THE POROUS FIBERS ACTUALLY PROMOTE PLANT GROWTH BY PROTECTING EMERGING PLANTS FROM RAIN IMPACT. VEGETATION EASILY PENETRATES THE MULCH MATRIX AND WILL ACTUALLY ENHANCE THE VISUAL APPEAL OF YOUR PROJECT.

### TIME AND LABOR SAVING

NOT ONLY WILL SPRAY GUARD® SMM CONFORM AND BOND SAFELY AND QUICKLY WITH DIFFICULT TERRAIN, IT ALSO SAVES TIME BECAUSE IT REQUIRES NO STAPLES OR NETTING. THE HYDRAULICALLY APPLIED EROSION BLANKET ALLOWS YOU TO SKIP TEDIOUS SOIL PREPARATION STEPS. AND YOU WON'T NEED TO HASSLE WITH SNIPPING NETTING OR POUNDING STAKES. IT'S QUICK, EASY, AND EFFECTIVE.

## Tech Specs

PRODUCT PROPERTIES HAVE BEEN DETERMINED USING SCIENTIFICALLY SOUND AND RELIABLE TEST METHODS. OTHER TEST METHODS MAY PRODUCE SLIGHTLY DIFFERENT RESULTS.

### INGREDIENTS:

WOOD FIBER CONTENT.....>89%  
GUAR GUM TACKIFIER CONTENT BY WEIGHT.....<4.5%  
SYNTHETIC FIBER CONTENT.....2.5%±1  
BASIC GREEN DYE.....<1%  
TRADE SECRET.....<1%  
TRADE SECRET.....<1%  
TRADE SECRET.....<1%

### COMPOSITION:

ORGANIC MATTER (MIN.).....97%  
INORGANIC MATTER (ASH) (MAX.).....3%  
MOISTURE CONTENT (TOTAL WEIGHT BASE).....12%±3%  
PH AT 3% CONSISTENCY IN WATER SLURRY (AVG.).....4.8  
WATER-HOLDING CAPACITY (MIN.).....1.2GAL./LB.

### COVERAGE:

3000-4000 LBS. /ACRE TO ACHIEVE 100% COVERAGE.

### PERFORMANCE

DRYING TIME.....12-24 HRS.  
LONGEVITY.....UP TO 6 MOS.  
DEPENDING ON SIGHT CONDITIONS

### PACKAGING AND SHIPPING

NET WT. 50 LBS. 22.6 KG. NET DRY WT. 44-45 LBS.

PACKAGED IN 50 LB. (22.6 KG.) PLASTIC OR  
MULTI-WALLED PAPER BAGS.

AVAILABLE IN PALLETIZED 36 BAG UNITS  
OR 18 BAG UNITS

PRODUCT CERTIFICATION AND MSDS AVAILABLE UPON REQUEST.