

Tacking Agent 3® - Tackifier

A Tackifier that requires no cure time!

- Tacking Agent 3 has long set the standard as an effective binding agent. It is proven to reduce soil erosion and water runoff immediately after hydroseeding—no cure time is required!
- Tacking Agent 3 contains a flocculant, polyacrylamide and hydro-colloid polymers for enhanced fiber-to-soil bond as well as a marker dye to enhance visual metering when the product is being applied



Hydraulic Fiber Mulch Binding - Slope Gradient/Condition Rate:

>2H:1V Slope 60lbs per acre

3H:1V Slope 40lbs per acre

4H:1V Slope 30lbs per acre

Modest to 5H :1V Slope 20lbs per acre

TANK LOADS	
300 gal	3 lb
500 gal	5 lb
900 gal	10 lb
1,500 gal	15 lb
3,000 gal	30 lb

Amendment Ingredients

Polyacrylamide
Acrylamide copolymer
Hydro-colloid polymers
Marker Dye

Packaging

4 – 8-lb bags per case/60 cases per pallet; 7 – 3-lb water soluble bags per case/56 cases per pallet; 40 – 50-lb bags/50 – 40-lb bags per pallet



**GREEN DESIGN
ENGINEERING™**
EARTH-FRIENDLY SOLUTIONS
FOR SUSTAINABLE RESULTS™



For more information, please contact us: 1 888 298-9911
www.fibramulch.com

